

InsuKure S

A polymer, water-based, concrete curing compound.

DESCRIPTION OF PRODUCT

InsuKure S is a solvent-free, polymer, water-based emulsion, suitable for spray application to freshly poured concrete.

The resultant film retains sufficient moisture in the concrete to ensure full hydration of the cement; essential for optimum strength development. Membrane-cured concrete is typically harder and exhibits a dust-free surface with a reduced incidence of drying shrinkage cracks.

PRIMARY USES

As a more effective and economical alternative to Hessian, water and polythene curing regimes. Suitable for use on all concrete surfaces.

ADVANTAGES

- Eliminates the need for water.
- Single application.
- Reduces drying shrinkage.
- High curing efficiency.
- Reduced labour costs ..
- Water-based.

PACKAGING

InsuKure S is available in 20 ltr and 200 ltr containers.

TYPICAL PROPERTIES

Appearance:	White liquid
Specific gravity:	Approx. 1.005 at 25°C
Flashpoint:	Not applicable
Finished film appearance:	Clear opaque film
Drying time	2.30 hours 20 minutes
ASTM C309:	at 25°C / dosage of 0.2kg/m ²

STANDARDS

InsuKure S meets the requirements of ASTM C309 Type 1 Class A

COVERAGE

The recommended rate of application is 0.2ltr/m². This corresponds to that at which **InsuKure S** has been tested, and at which it attains the claimed degree of curing efficiency. In favorable conditions, such as shaded interior surfaces, adequate curing can be achieved with extended coverage rates.

SUBSEQUENT SURFACE FINISHES

It is important to ensure the complete removal of the InsuKure S prior to the application of any surface finish or additional treatment.

InsuLatex bonding slurries must be utilised to bond subsequent finishes. Please refer to Insumat's Technical Services Department for approved mix designs.

If renders of greater thickness than 1cm are to be applied, bond tests should be carried out to determine the proposed bonding method and surface preparation that is required. For floor areas, the curing compound must be removed prior to applying subsequent finishes.

SPECIFICATION CLAUSE InsuKure S

Where indicated, concrete shall be cured by application of InsuKure S, polymer-based emulsion manufactured by Insumat Egypt or similar approved; to the following specification.

SPECIFICATION TYPE

ASTM C309: Type 1 Class A InsuKure S is to be applied strictly in accordance with the manufacturer's instructions.

STORAGE

Shelf life is up to 1 year when stored under cover, out of direct sunlight and protected from extremes of temperature.

InsuKure S

A polymer, water-based, concrete curing compound.

HEALTH AND SAFETY

As with all chemical products, care should be taken, during use and storage, to avoid contact with eyes, mouth, skin and foodstuffs. Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Re-seal containers after use. Use in well-ventilated areas and avoid inhalation.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information, contact Insumat's representative.

Insumat reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY STATEMENT

All products manufactured by Insumat Egypt, are manufactured to procedures certified to conform to the quality, environment, health & safety management systems described in the ISO 9001:2015, standard.

* Properties listed are based on laboratory controlled tests.

Actual measured data may vary due to circumstances beyond Insumat's control.

Manufacturing Insulating Materials and Products Company

Founded by
Osman Ahmed Osman
1974

☎ 011 1974 1974
📍 Plot 83 El Motawereen - El Sadat City - Menofia
✉ info@insumat.com
🌐 www.insumat.com